

Material Safety Data Sheet

SURECOTE 500 SUBFILL PART A

Infosafe ACRLN No. **Version No.** **ISSUED Date** July 2008 **Status** ISSUED
by
NUPLEXIN

Classified as hazardous according to criteria of NOHSC

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name

SURECOTE 500 SUBFILL PART A

Product Code

B84398

Company Name

Nuplex Industries (Aust) Pty Ltd (ABN 25 000 045 572)

Address

49-61 Stephen Road, Botany, NSW 2019

New Zealand: Nuplex Industries Ltd., 12 Industry Road, Penrose, Auckland

Emergency Tel.

Australia: 1800 022 037 (24H); New Zealand: 0800 154 666 (24H)

Telephone/Fax Number

Tel: Australia: (02) 9839 4000; New Zealand: (09) 579 2029 Fax: Australia: (02) 9674 6225; New Zealand: (09) 525 1618

Recommended Use

Construction product.

Other Names

Not Available

2. HAZARDS IDENTIFICATION

Hazard Classification

Australia:

Classified as Hazardous according to criteria of National Occupational Health & Safety Commission, Australia (NOHSC).

Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail.

New Zealand:

Classified as Hazardous according to the New Zealand Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001.

Classified as Dangerous Goods for transport according to the NZS 5433:2007 Transport of Dangerous Goods on Land.

HSNO Classification:

6.1D - Substance that is acutely toxic.

6.3A - Substance that is irritating to the skin.

6.4A - Substance that is irritating to the eye.

6.5B - Substance that is a contact sensitiser.

- 9.1B - Substance that is ecotoxic in the aquatic environment.
 9.3C - Substance that is harmful to terrestrial vertebrates.

Hazard statement code:

- H302 Harmful if swallowed.
 H315 Causes skin irritation.
 H320 Causes eye irritation.
 H317 May cause an allergic skin reaction.
 H411 Toxic to aquatic life with long lasting effects.
 H433 Harmful to terrestrial vertebrates.

Precautionary statement codes- prevention:

- P102 Keep out of reach of children.
 P103 Read label before use. - This statement applies only where the substance is available to the general public.
 P104 Read Safety Data Sheet before use.
 P261 Avoid breathing mist/vapours/spray.
 P264 Wash hands thoroughly after handling.
 P270 Do not eat, drink or smoke when using this product.
 P272 Contaminated work clothing should not be allowed out of the workplace.
 P280 Wear protective gloves/eye protection.
 P273 Avoid release to the environment.

Precautionary statement codes- response:

- P101 If medical advice is needed, have product container or label at hand. - This statement applies only where the substance is available to the general public.
 P301+P312 IF SWALLOWED: Call a POISON CENTRE or doctor/physician if you feel unwell.
 P330 Rinse mouth.
 P331 Do NOT induce vomiting.
 P302+P352 IF ON SKIN: Wash with plenty of soap and water.
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 P362 Take off contaminated clothing and wash before re-use.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P337+P313 If eye irritation persists: Get medical advice/attention.
 P391 Collect spillage.

Precautionary statement codes - Storage:

No storage statements.

Precautionary statement codes - Disposal:

P501 In the case of a substance that is in compliance with a HSNO approval other than a Part 6A (Group Standards) approval, a label must provide a description of one or more appropriate and achievable methods for the disposal of a substance in accordance with the Hazardous Substances (Disposal) Regulations 2001. This may also include any method of disposal that must be avoided.

Risk Phrase(s)

- R43 May cause sensitization by skin contact.
 R36/38 Irritating to eyes and skin.
 R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety Phrase(s)

- S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
 S28 After contact with skin, wash immediately with plenty of soap and water.
 S61 Avoid release to the environment. Refer to special instructions/safety data sheets.
 S62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.
 S24/25 Avoid contact with skin and eyes.
 S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients

Name	CAS	EINECS	Proportion
Bisphenol A epoxy resin	25085-99-8		60-90 %
Alkyl glycidyl ether	68609-97-2	271-846-10-30	%

8

Other ingredients
determined not to be
hazardous

(To 100%)

4. FIRST AID MEASURES

Inhalation

Remove affected person from exposure. Allow to assume most comfortable position and keep warm. Keep at rest until fully recovered. If symptoms persist seek medical attention.

Ingestion

If swallowed do NOT induce vomiting. Wash out mouth with water. Do not give anything by mouth to an unconscious person. Seek immediate medical attention.

Skin

If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Seek medical attention.

Eye

If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Seek immediate medical attention.

First Aid Facilities

Eye wash station, safety shower and normal washroom facilities.

Advice to Doctor

Treat symptomatically.

Other Information

For advice in an emergency, contact a Poisons Information Centre (Phone eg Australia 13 1126; New Zealand 0800 POISON / 0800 764 766) or a doctor.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media

Foam, dry chemical powder, carbon dioxide, water spray or water fog.

Hazards from Combustion Products

Under fire conditions this product will emit toxic and/or irritating fumes including carbon monoxide and carbon dioxide.

Specific Hazards

Combustible liquid. This product will burn if exposed to fire. Drums may rupture when exposed to fire conditions.

Hazchem Code

•3Z

Precautions in connection with Fire

Fire fighters should wear Self-Contained Breathing Apparatus (SCBA) and full protective clothing to prevent exposure to vapours, fumes or products of combustion. Water spray may be used to cool down heat-exposed containers

6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures

Increase ventilation. Evacuate all unnecessary personnel. Wear protective clothing and equipment to prevent exposure. If possible contain the spill. Place inert absorbent such as vermiculite or sand onto material. Prevent run off into drains and

waterways. Use clean non-sparking tools to collect the material and place into suitable, labelled containers. Dispose of waste in accordance with applicable local and national regulations. If spillage enters the waterways inform the EPA and the local water authorities.

7. HANDLING AND STORAGE

Handling and Storage

Classified as a Class C2 (COMBUSTIBLE LIQUID) for the purpose of storage and handling, in accordance with the requirements of AS1940. This product should be stored and used in a well ventilated area away from naked flames, sparks and other sources of ignition.

Precautions for Safe Handling

Use in a well ventilated area. Wear appropriate protective clothing and equipment to prevent skin, eye and respiratory exposure. Avoid generating vapours or mist. Label containers and keep closed when not in use. Empty containers may contain residues that are hazardous.

Conditions for Safe Storage

Store in a cool, dry, well ventilated area away from sources of ignition. This product should be stored away from foodstuffs, strong oxidising agents and aliphatic amines. For information on the design of the store-room reference should be made to Australian Standard AS1940, The storage and handling of flammable and combustible liquids. Reference should also be made to applicable Commonwealth, State and Territory regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

National Exposure Standards

No exposure standards have been established for this material by the Australian National Occupational Health & Safety Commission (NOHSC) or the Occupational Safety and Health Service (OSH) of the New Zealand Department of Labour. However, over-exposure to some chemicals may result in enhancement of pre-existing adverse medical conditions and/or allergic reactions and should be kept to the least possible levels.

Engineering Controls

Use with good general ventilation. Where vapours or mists are generated, a local exhaust ventilation system, drawing vapours/mists away from workers breathing zone, should be used.

Respiratory Protection

If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable vapour/mist filter should be used. Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

Eye Protection

Safety glasses with side shields or goggles should be worn as described in Australian Standard AS/ANZ 1337 - Eye Protectors for Industrial Applications.

Hand Protection

Wear laminated film or other suitable gloves conforming to AS/NZS 2161: Occupational protective gloves. Final choice of appropriate glove type will vary according to individual circumstances. This can include methods of handling, and engineering controls as determined by appropriate risk assessments.

Body Protection

Suitable protective workwear, e.g. cotton overalls buttoned at neck and wrist. Industrial clothing should conform to the specifications detailed in AS/NZS 2919: Industrial clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Clear liquid with a mild odour.

Melting Point

Not available

Boiling Point

>200°C

Solubility in Water

Insoluble

Specific Gravity

1.15

Vapour Pressure

Not available

Vapour Density (Air=1)

>1 (Air=1)

Viscosity

Not available

Volatile Component

<1%

Flash Point

154°C (PMCC)

Flammability

Combustible liquid.

Auto-Ignition Temperature

Not available

Flammable Limits - Lower

Not available

Flammable Limits - Upper

Not available

10. STABILITY AND REACTIVITY

Chemical Stability

Stable under normal conditions of storage and handling.

Incompatible Materials

Strong oxidizing agents, acids, bases and amines.

Hazardous Decomposition Products

Oxides of carbon.

Hazardous Polymerization

May occur at elevated temperatures or if a large amount (>0.5 kg) is mixed with an aliphatic amine.

11. TOXICOLOGICAL INFORMATION

Toxicology Information

LD50 (Oral, Rat): >5,000 mg/kg

Inhalation

Inhalation of product vapours may cause irritation to the nose, throat and other parts of the respiratory system.

Ingestion

Ingestion of this product may irritate the gastric tract causing nausea, vomiting and abdominal pain.

Skin

Irritating to skin. Skin contact may cause redness and itching. May cause sensitisation by skin contact.

Eye

Irritating to eyes. On eye contact this product will cause tearing, stinging, blurred vision, and redness.

Chronic Effects

Prolonged or repeated skin contact may lead to allergic contact dermatitis and sensitisation in some individuals.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Persistence / Degradability

Not available

Mobility

Not available

Bioaccumulative Potential

Not available

Environ. Protection Do not allow product to enter drains, waterways or sewers.

13. DISPOSAL CONSIDERATIONS

Disposal Considerations

The disposal of the spilled or waste material must be done in accordance with applicable local and national regulations.

14. TRANSPORT INFORMATION

Transport Information**Australia:**

This material is classified as a Class 9 (Miscellaneous Dangerous Goods) Dangerous Good according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. Dangerous goods of Class 9 (Miscellaneous Dangerous Goods) are incompatible in a placard load with any of the following:

- Class 1, Explosive
- Class 5.1, if the Class 9 substance is a fire risk substance
- Class 5.2, if the Class 9 substance is a fire risk substance

New Zealand:

This material is classified as a Class 9 - Miscellaneous Substance according to NZS 5433:2007 Transport of Dangerous Goods on Land.

Must not be loaded in the same freight container or on the same vehicle with:

- Class 1, Explosives
Goods of packing group II or III may be loaded in the same freight container or on the same vehicle if transported in segregation devices with:
(Note 3; Segregation devices may be used as to segregate dangerous goods of Class 9 when the nature of those dangerous goods requires them to be segregated from dangerous goods of);
- Class 3, Flammable liquids
- Class 4.1, Flammable solids
- Class 4.2, Spontaneously combustible substances
- Class 4.3, Dangerous when wet substances
- Class 5.1, Oxidising substances
- Class 5.2, Organic peroxides
- Class 6.1, Toxic substances
- Class 6.2, Infectious substances
- Class 8, Corrosive substances
And are incompatible with food and food packaging in any quantity.

U.N. Number

3082

Proper Shipping Name

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. - (CONTAINS: BISPHENOL A EPOXY RESINS)

DG Class

9

Hazchem Code

•3Z

Packing Group

III

IERG Number

47

15. REGULATORY INFORMATION

Regulatory Information**Australia:**

Classified as Hazardous according to criteria of National Occupational Health & Safety Commission, Australia (NOHSC).

Classified as a Scheduled Poison S5, according to the Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).

Poisons Schedule

S5

National and or International Regulatory Information**New Zealand:**

Classified as Hazardous according to the New Zealand Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001.

Group Standard:

Surface Coatings and Colourants (Subsidiary Hazard) Group Standard 2006

HSNO Approval Number: HSR002670.

All components of this product are listed on the New Zealand Inventory of Chemicals (NZIC).

Hazard Category

Irritant, Dangerous for the environment, Sensitising

AICS (Australia)

All constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Date of preparation or last revision of MSDS

MSDS Reviewed: July 2008

Supersedes: July 2003

Contact Person/Point

Paul Verren For specialist advice in emergencies: Australia 1800 022 037; New Zealand 0800 154 666.

IMPORTANT ADVICE: This MSDS summarizes our best knowledge of the health and safety hazard information of the product and how to safely handle and use the product in the workplace. Each user should read this MSDS and consider the information in the context of how the product will be handled and used in the workplace including its use in conjunction with other products. If clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact Nuplex Industries (Aust) Pty Ltd. Our responsibility for products sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available on request.

NUPLEX MSDS WARNING: Nuplex Group (Nuplex) is aware that third parties are distributing documents purporting to be MSDSs (or the like) in relation to Nuplex products without any authorisation from Nuplex (Unauthorised MSDS). Nuplex accepts no responsibility for the distribution of an Unauthorised MSDS by a third party. All Nuplex products must be used in accordance with the corresponding original MSDS authorised by Nuplex for use with that Nuplex product (Authorised MSDS). In the event a Nuplex product is used without the Authorised MSDS and/or with an Unauthorised MSDS, Nuplex hereby excludes absolutely and to the maximum extent permitted by law all liability whatsoever and howsoever arising for all loss and/or damage including but not limited to for personal injury, sickness and death, damage to real property and chattels and direct and indirect consequential loss and loss of profits.

End of MSDS
